

Cisco

300-070

Implementing Cisco IP Telephony & Video, Part 1 v1.0

For More Information – Visit link below:

<http://www.examsboost.com/>

Product Version

Question: 1

Which route pattern wildcard character is used to terminate the interdigit timeout?

- A. \$
- B. !
- C. #
- D. .

Answer: C

Question: 2

When a call is attempted during a particular time of day, what determines the partitions where calling devices search?

- A. time schedules
- B. calling periods
- C. dial schedules
- D. time periods

Answer: A

Question: 3

When configuring an H.323 gateway, which configuration option can be used to set whether an incoming call is considered off the network (OffNet) or on the network (OnNet)?

- A. call classification
- B. call location
- C. device pool
- D. signaling port

Answer: A

Question: 4

When local route groups are used and a user dials 918005551212, what component is ultimately used to route the digits to the local gateway?

- A. The route list applied to the route pattern
- B. The device pool of the calling device
- C. The translation pattern
- D. The gateway or route list associated with the +.! route pattern

Answer: B

Question: 5

You are performing route pattern configuration. You need to ensure that internal extensions are automatically expanded to full external phone numbers for calling line information on outgoing calls. What should you use?

- A. calling extension expansion
- B. called number expansion
- C. external number mask of the called party
- D. external phone number mask of the calling party

Answer: D

Question: 6

The CSS on a line includes the partitions 911, internal and local. The CSS on the device includes the partitions 911, internal, local and long distance. Which CSS will be used if the phone user dials a local number?

- A. The device CSS will be used since the device CSS is always used first on an IP phone.
- B. Since the dialed digits are a match to a partition in both Calling Search Spaces the call will use both matched partitions in both Calling Search Spaces in a round-robin format.
- C. If there is both a line and device CSS the line device will only be used.
- D. The line and device CSSs will be combined and the device CSS will take precedence.
- E. The line and device CSSs will be combined and the line CSS will take precedence.

Answer: E

Question: 7

What are two characteristics of a partition? (Choose two.)

- A. Assigned to sources of call routing requests
- B. Any group of numbers with the same reachability
- C. Used in conjunction with calling search spaces to track calls to certain numbers
- D. Used in conjunction with calling search spaces to restrict outgoing calls to certain numbers
- E. Contains calling search spaces

Answer: B,D

Question: 8

Which two statements about Cisco VCS Addressing Zones are true? (Choose two.)

- A. They can be local to the Cisco VCS or can be remote.
- B. A zone is a collection of endpoints that share the same dialing behavior and bandwidth settings.
- C. They consist of traversal and nontraversal zones.
- D. They can only be local.
- E. They consist of subzones such as DNS zones.

Answer: A,B

Question: 9

Which four call coverage features are used by voice gateways? (Choose four.)

- A. call hunt
- B. Call Park
- C. Call Pickup
- D. call redirecting
- E. overlaid phone-dn
- F. basic automatic call distribution
- G. overlaid ephone-dn
- H. basic manual call distribution

Answer: A,C,F,G

Question: 10

Refer to the exhibit.

Translation Pattern Configuration

Save

Status
i Status: Ready

Pattern Definition
Translation Pattern 0.001
Partition < None >
Description
Numbering Plan NANP
Route Filter < None >
MLPP Precedence* Par défaut
Resource Priority Namespace Network Domain < None >
Route Class* Par défaut
Calling Search Space No_restriction
External Call Control Profile < None >
Route Option
☒ Route this pattern
☐ Block this pattern Aucune erreur
☒ Provide Outside Dial Tone
☐ Urgent Priority
☐ Route Next Hop By Calling Party Number

Route Pattern Configuration

Save

Status
i Status: Ready

Pattern Definition
Route Pattern* 0.0044156789453
Route Partition < None >
Description
Numbering Plan -- Not Selected --
Route Filter < None >
MLPP Precedence* Par défaut
☐ Apply Call Blocking Percentage
Resource Priority Namespace Network Domain < None >
Route Class* Par défaut
Gateway/Route List* RL_TEST (Edit)
Route Option
☒ Route this pattern
☐ Block this pattern Aucune erreur
Call Classification* OffNet
☐ Allow Device Override ☒ Provide Outside Dial Tone ☐ Allow Overlap Sending ☐ Urgent Priority
☐ Require Forced Authorization Code
Authorization Level* 0
☐ Require Client Matter Code

When users call number 00044156789453, they have to wait for several seconds before the call is sent. Which action sends the call immediately?

- A. In the translation pattern, change the CSS.
- B. In the route pattern, check the Allow Device Override check box.
- C. In the route pattern, check the Urgent Priority check box.
- D. In the translation pattern, check the Route Next Hop By Calling Party Number check box.

Answer: C

Question: 11

Which three options are valid SIP URI formats? (Choose three.)

- A. jsmith@cisco.com
- B. tel:98765@cisco.com
- C. phone:98765@cisco.com
- D. sip:12345@10.10.10.10:5060;user=phone
- E. sip:bob.cisco.com

Answer: A,B,D

Question: 12

Which two Cisco products allow the use of a dial plan with E.164, H.323, SIP, and DNS? (Choose two.)

- A. Cisco Expressway
- B. Cisco Unified Communications Manager
- C. Cisco Unified Border Element
- D. Cisco IM and Presence
- E. Cisco TelePresence Video Communication Server

Answer: A,E

Thank You for Trying Our Product

For More Information – **Visit link below:**

<http://www.examsboost.com/>

FEATURES

- ✓ **90 Days Free Updates**
- ✓ **Money Back Pass Guarantee**
- ✓ **Instant Download or Email Attachment**
- ✓ **24/7 Live Chat Support**
- ✓ **PDF file could be used at any Platform**
- ✓ **50,000 Happy Customer**



WE ACCEPT

